

R-Style High Flow Tubes

PCS Company's R-Style High Flow Tubes are constructed of stainless steel for strength and durability. The R-Style tubes are designed to be installed from alternate directions and after the plates have been assembled for ease of maintenance and inspection. Available in standard lengths of 12", 18, 24" and 36".



Features:

- All stainless construction for high strength and durability
- Hex wrench installation
- Threads to shoulder for positive positioning
- Can install from alternate directions, even after plates are assembled, for easier maintenance, and quicker inspections.
- Standard length 12, 18, 24 and 36 inches
- NPT Threads
- Unit of Measure - Inch



| Item Number | Thread Size | Tube O.D. | Tube I.D. | Wrench Size | H Head Height | A Length | D Dia. | OAL |
|-------------|-------------|-----------|-----------|-------------|---------------|----------|--------|-----|
| R072T-12 | 5-44 | .072 | .060 | 1/8 | .156 | .312 | .182 | 12 |
| R072T-18 | 5-44 | .072 | .060 | 1/8 | .156 | .312 | .182 | 18 |
| R072T-24 | 5-44 | .072 | .060 | 1/8 | .156 | .312 | .182 | 24 |
| R072T-36 | 5-44 | .072 | .060 | 1/8 | .156 | .312 | .182 | 36 |
| JR072T-12 | 10-32 | .072 | .060 | 1/8 | .187 | .406 | .245 | 12 |
| JR072T-18 | 10-32 | .072 | .060 | 1/8 | .187 | .406 | .245 | 18 |
| JR072T-24 | 10-32 | .072 | .060 | 1/8 | .187 | .406 | .245 | 24 |
| JR072T-36 | 10-32 | .072 | .060 | 1/8 | .187 | .406 | .245 | 36 |
| R090T-12 | 5-44 | .090 | .076 | 1/8 | .156 | .312 | .182 | 12 |
| R090T-18 | 5-44 | .090 | .076 | 1/8 | .156 | .312 | .182 | 18 |
| R090T-24 | 5-44 | .090 | .076 | 1/8 | .156 | .312 | .182 | 24 |
| R090T-36 | 5-44 | .090 | .076 | 1/8 | .156 | .312 | .182 | 36 |
| JR090T-12 | 10-32 | .090 | .076 | 1/8 | .187 | .406 | .245 | 12 |
| JR090T-18 | 10-32 | .090 | .076 | 1/8 | .187 | .406 | .245 | 18 |
| JR090T-24 | 10-32 | .090 | .076 | 1/8 | .187 | .406 | .245 | 24 |
| JR090T-36 | 10-32 | .090 | .076 | 1/8 | .187 | .406 | .245 | 36 |
| R125T-12 | 10-32 | .125 | .109 | 5/32 | .187 | .406 | .245 | 12 |
| R125T-18 | 10-32 | .125 | .109 | 5/32 | .187 | .406 | .245 | 18 |
| R125T-24 | 10-32 | .125 | .109 | 5/32 | .187 | .406 | .245 | 24 |
| R125T-36 | 10-32 | .125 | .109 | 5/32 | .187 | .406 | .245 | 36 |
| JR125T-12 | 1/4-28 | .125 | .109 | 5/32 | .187 | .406 | .307 | 12 |
| JR125T-18 | 1/4-28 | .125 | .109 | 5/32 | .187 | .406 | .307 | 18 |
| JR125T-24 | 1/4-28 | .125 | .109 | 5/32 | .187 | .406 | .307 | 24 |
| JR125T-36 | 1/4-28 | .125 | .109 | 5/32 | .187 | .406 | .307 | 36 |

R-Style High Flow Tubes

PCS Company's R-Style High Flow Tubes are constructed of stainless steel for strength and durability. The R-Style tubes are designed to be installed from alternate directions and after the plates have been assembled for ease of maintenance and inspection. Available in standard lengths of 12", 18, 24" and 36".



Features:

- All stainless construction for high strength and durability
- Hex wrench installation
- Threads to shoulder for positive positioning
- Can install from alternate directions, even after plates are assembled, for easier maintenance, and quicker inspections.
- Standard length 12, 18, 24 and 36 inches
- NPT Threads
- Unit of Measure - Inch



| Item Number | Thread Size | Tube O.D. | Tube I.D. | Wrench Size | H Head Height | A Length | D Dia. | OAL |
|-------------|-------------|-----------|-----------|-------------|---------------|----------|--------|-----|
| R187T-12 | 1/4/28 | .187 | .167 | 3/16 | .250 | .500 | .307 | 12 |
| R187T-18 | 1/4/28 | .187 | .167 | 3/16 | .250 | .500 | .307 | 18 |
| R187T-24 | 1/4/28 | .187 | .167 | 3/16 | .250 | .500 | .307 | 24 |
| R187T-36 | 1/4/28 | .187 | .167 | 3/16 | .250 | .500 | .307 | 36 |
| JR187T-12 | 5/16-24 | .187 | .167 | 1/4 | .281 | .562 | .370 | 12 |
| JR187T-18 | 5/16-24 | .187 | .167 | 1/4 | .281 | .562 | .370 | 18 |
| JR187T-24 | 5/16-24 | .187 | .167 | 1/4 | .281 | .562 | .370 | 24 |
| JR187T-36 | 5/16-24 | .187 | .167 | 1/4 | .281 | .562 | .370 | 36 |
| R250T-12 | 5/16-24 | .250 | .230 | 1/4 | .281 | .562 | .370 | 12 |
| R250T-18 | 5/16-24 | .250 | .230 | 1/4 | .281 | .562 | .370 | 18 |
| R250T-24 | 5/16-24 | .250 | .230 | 1/4 | .281 | .562 | .370 | 24 |
| R250T-36 | 5/16-24 | .250 | .230 | 1/4 | .281 | .562 | .370 | 36 |
| JR250T-12 | 3/8-24 | .250 | .230 | 5/16 | .312 | .625 | .495 | 12 |
| JR250T-18 | 3/8-24 | .250 | .230 | 5/16 | .312 | .625 | .495 | 18 |
| JR250T-24 | 3/8-24 | .250 | .230 | 5/16 | .312 | .625 | .495 | 24 |
| JR250T-36 | 3/8-24 | .250 | .230 | 5/16 | .312 | .625 | .495 | 36 |
| R312T-12 | 3/8-24 | .312 | .288 | 5/16 | .312 | .625 | .495 | 12 |
| R312T-18 | 3/8-24 | .312 | .288 | 5/16 | .312 | .625 | .495 | 18 |
| R312T-24 | 3/8-24 | .312 | .288 | 5/16 | .312 | .625 | .495 | 24 |
| R312T-36 | 3/8-24 | .312 | .288 | 5/16 | .312 | .625 | .495 | 36 |
| JR312T-12 | 1/2-20 | .312 | .288 | 3/8 | .375 | .750 | .620 | 12 |
| JR312T-18 | 1/2-20 | .312 | .288 | 3/8 | .375 | .750 | .620 | 18 |
| JR312T-24 | 1/2-20 | .312 | .288 | 3/8 | .375 | .750 | .620 | 24 |
| JR312T-36 | 1/2-20 | .312 | .288 | 3/8 | .375 | .750 | .620 | 36 |