SAFETY DATA SHEET.

Issuing date 25-Jan-2022

Revision Date 26-Jan-2022

Version 1

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

<u>Product identifier</u> Product name	DMP 1610 DRY MOLD PROTECTOR
Recommended use of the chemical and restrictions on use	-
Product code	F04427
<u>Product Type</u> Synonyms	Extremely Flammable Aerosol None
Supplier's details	
Recommended Use	Mold Shield Dry Rust Preventive.
Uses advised against	No information available
Manufactured For: PCS Company 34500 Doreka Drive Fraser, MI 48206 PHONE;1-800-521-0546 M-F 8A-5P	Manufacturer American Jetway Corporation 34136 Myrtle Street Wayne, MI 48184-0126 Phone:(734) 721-5930
Emergency telephone number Chemical Emergency Phone Number	CHEMTREC: 1-800-262-8200 ID 1195 (UNITED STATES)

2. HAZARDS IDENTIFICATION

Classification

Skin corrosion/irritation	Category 2
Specific target organ toxicity (single exposure)	Category 3
Aspiration toxicity	Category 1
Flammable Aerosols	Category 1
Gases under pressure	Compressed Gas

GHS Label elements, including precautionary statements

Emergency Overview

DANGER

Hazard Statements

Causes skin irritation. May cause respiratory irritation. May cause drowsiness or dizziness. May be fatal if swallowed and enters airways. Extremely Flammable Aerosol Contains gas under pressure; may explode if heated



Appearance Hazy

Physical state Aerosol

Odor Solvent

Precautionary Statements - Prevention

Wash face, hands and any exposed skin thoroughly after handling. Wear protective gloves. Avoid breathing fumes, gas, mist, vapors, spray. Use only outdoors or in a well-ventilated area. Keep away from heat, sparks, open flames, hot surfaces - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use.

Precautionary Statements - Response

Specific treatment (see first aid on this label). IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs: Get medical advice, attention. Take off contaminated clothing and wash it before reuse. IF INHALED : Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor, physician if you feel unwell. IF SWALLOWED: Immediately call a POISON CENTER, doctor, physician. Do NOT induce vomiting.

Precautionary Statements - Storage

Store locked up. Store in a well-ventilated place. Keep container tightly closed. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

Precautionary Statements - Disposal

Dispose of contents, container to an approved waste disposal plant.

Hazards not otherwise classified (HNOC)

None

Other information

0% of the mixture consists of ingredient(s) of unknown toxicity.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No	Weight %*
HEPTANE	142-82-5	60-70
PROPANE/ISOBUTANE/N-BUTANE	68476-86-8	30-40
PETROLEUM DISTILLATES	8052-41-3	0.1-1.0

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

First aid measures for different exposure routes

General advice	Avoid contact with eyes, skin, and clothing. Avoid breathing vapors, mist or gas.
Eye contact	In the case of contact with eyes, rinse immediately with plenty of water for 15 minutes and seek medical advice.
Skin contact	Wash off immediately with soap and plenty of water for at least 15 minutes. Get medical attention immediately if symptoms occur.
Inhalation	Move to fresh air. If not breathing, give artificial respiration. If breathing has stopped, contact emergency medical services immediately.
Ingestion	Do NOT induce vomiting. Call a physician immediately. Never give anything by mouth to unconscious person. Risk of product entering the lungs on vomiting after ingestion.
Most important symptoms/effects,	acute and delayed
Main Symptoms	Causes skin irritation. May cause eye and respiratory irritation. May cause drowsiness or dizziness. Harmful and may be fatal if swallowed.
Indication of immediate medical attention and special treatment needed, if necessary	
Notes to physician	Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Water fog. Carbon Dioxide (CO2), Foam, Dry Chemical. Cool Tanks/ containers with water spray.

Unsuitable Extinguishing Media Do not use a solid water stream as it may scatter and spread fire.

Specific hazards arising from the chemical

Extremely Flammable / Flammable. Keep product and empty container away from heat and sources of ignition.

Explosion Data Sensitivity to Mechanical Impact none. Sensitivity to Static Discharge Yes.

F04427 - DMP 1610 DRY MOLD PROTECTOR

Protective Equipment and Precautions for Firefighters

In the event of fire and/or explosion do not breathe fumes. As in any fire, wear self-contained breathing apparatus pressure-demand. MSHA/NIOSH (approved or equivalent) and full protective gear. Use shielding to protect fire-fighters from bursting containers.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions	Use with adequate ventiliation to keep the exposure levels below the OELS.
Environmental precautions	
Environmental precautions	Vapors can accumulate in low areas. Prevent further leakage or spillage if safe to do so. Do not allow material to contaminate ground water system. Prevent product from entering drains. Report spills as required by local and federal regulations.
Methods and materials for cont	ainment and cleaning up
Methods for Containment	Prevent further leakage or spillage if safe to do so. Do not allow material to contaminate ground water system. Prevent product from entering drains.
Methods for cleaning up	Soak up with inert absorbent material. Contain liquid and collect with an inter, non-combustible material. Pick up and transfer to properly labeled containers. Clean contaminated surface thoroughly. After cleaning, flush away traces with water. Prevent product from entering drains. Take precautionary measures against static discharges.

Precautions for safe handling

Advice on safe handling Avoid contact with eyes. Avoid breathing vapors or mists. Contents under pressure. Do not puncture or incinerate cans. Do not stick pin or any other sharp object into opening on top of can. Avoid skin contact. Use with adequate ventilation. Keep container away from heat, flames, and all other sources of ignition. Keep can away from all sources of electricity such as electric motors and batteries. Do not spray on hot surfaces.

Conditions for safe storage, including any incompatibilities

Technical measures/Storage conditions	Keep container tightly closed in a dry and well-ventilated place. Keep away from open flames, hot surfaces, and sources of ignition. Keep in properly labeled containers. Keep out of the reach of children. Store locked up.
Incompatible products	Strong acids, alkalis, oxidizing agents.
Aerosol Level	3

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
HEPTANE	STEL: 500 ppm	TWA: 500 ppm	IDLH: 750 ppm
142-82-5	TWA: 400 ppm	TWA: 2000 mg/m ³	Ceiling: 440 ppm 15 min
		(vacated) TWA: 400 ppm	Ceiling: 1800 mg/m ³ 15 min
		(vacated) TWA: 1600 mg/m ³	TWA: 85 ppm
		(vacated) STEL: 500 ppm	TWA: 350 mg/m ³
		(vacated) STEL: 2000 mg/m ³	_
PROPANE/ISOBUTANE/N-BUTANE	74-98-6: TWA: 1000 ppm	74-98-6:TWA: 1000 ppm	74-98-6:IDLH: 2100 ppm
68476-86-8	106-97-8: STEL: 1000 ppm	TWA: 1800 mg/m ³	TWA: 1000 ppm
	75-28-5: STEL: 1000 ppm	(vacated) TWA: 1000 ppm	TWA: 1800 mg/m ³
		(vacated) TWA: 1800 mg/m ³	106-97-8:TWA: 800 ppm

F04427 - DMP 1610 DRY MOLD PROTECTOR

Revision Date 26-Jan-2022

		106-97-8: (vacated) TWA: 800	TWA: 1900 mg/m ³
		ppm (vacated) TWA: 1900 mg/m ³	75-28-5:TWA: 800 ppm TWA: 1900 mg/m ³
PETROLEUM DISTILLATES	TWA: 100 ppm	TWA: 500 ppm	IDLH: 20000 mg/m ³
8052-41-3		TWA: 2900 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 525 mg/m ³	Ceiling: 1800 mg/m ³ 15 min TWA: 350 mg/m ³
ACGIH: (American Conference of Ge OSHA: (Occupational Safety & Healt NIOSH IDLH: Immediately Dangerou	h Administration)		
Other Exposure Guidelines	Vacated limits revoked by the (11th Cir., 1992).	e Court of Appeals decision in AF	E-CIO v. OSHA, 965 F.2d 962
Exposure controls			
Engineering Measures	Showers Eyewash stations Ventilation systems.		
Individual protection measures, su	ch as personal protective equ	<u>uipment</u>	
Eye/Face Protection	Safety glasses with side-shiel	lds. Tightly fitting safety goggles	
Skin and body protection	Chemical resistant apron. Pro	ptective gloves.	
Respiratory protection	respiratory protection should	ed or irritation is experienced, NI be worn. Positive-pressure supp ntaminant concentrations. Respi current local regulations.	blied air respirators may be
Hygiene measures	Handle in accordance with go	ood industrial hygiene and safety	practice.
	9. PHYSICAL AND CHEM	ICAL PROPERTIES	
Physical and chemical properties			
Physical state	Aerosol		
Appearance	Hazy	Odor	Solvent
Color	Amber	Odor Threshold	
Property_	Values	Remarks • Methods	
pH	No information available	<u>Romanico</u> Motriodo	-
Melting/freezing point	No information available		
Boiling point/boiling range			
Flash Point	-96.4 °C / -141 °F	Based on propellant	
Evaporation rate Flammability (solid, gas) Flammability Limits in Air	No information available No information available		
upper flammability limit lower flammability limit			
Vapor pressure Vapor density			
Specific Gravity Water solubility	0.655 Practically insoluble		

vapor densitySpecific Gravity0.655Water solubilityPractically insolublePartition coefficient: n-octanol/waterAutoignition temperatureNo information availableDecomposition temperatureViscosityViscosityNo information available

Explosive properties

Other information

Not applicable

VOC Content(%) MIR Value MIR Coating Category 96.29 0.93 MRC - Mold Release Coating MAX 1.10 MIR

10. STABILITY AND REACTIVITY

Reactivity

No data available

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Conditions to Avoid

Heat, flames and sparks.

Incompatible Materials

Strong acids, alkalis, oxidizing agents.

Hazardous Decomposition Products

Carbon oxides , Hydrocarbons, Fumes.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Inhalation	Avoid inhaling vapors or mists. Harmful if inhaled. May cause irritation to respiratory system.
Eye contact	May be irritating to the eyes.
Skin contact	Causes skin irritation.
Ingestion	Harmful and may be fatal if swallowed and enters airways and lungs.

Component Information

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
HEPTANE 142-82-5	-	= 3000 mg/kg (Rabbit)	= 103 g/m³(Rat)4 h
PETROLEUM DISTILLATES 8052-41-3	-	> 3000 mg/kg (Rabbit)	-

Information on toxicological effects

SymptomsCauses skin irritation. May cause eye and respiratory irritationMay cause dizziness or
drowsiness.drowsiness.Harmful and may be fatal if swallowed and enters airways.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Eye damage/irritation Irritation	Causes skin irritation. May cause eye irritation. Causes skin irritation. May cause eye and respiratory irritation.
Sensitization	No information available.
Germ cell mutagenicity	Not a germ cell mutagen.
Carcinogenicity	This product does not contain any carcinogens.
Reproductive toxicity	This product does not contain a chemical(s) which is a known or suspected reproductive hazard .

Specific target organ systemic toxicity (single exposure)	May cause respiratory irritation. May cause drowsiness or dizziness.
Specific target organ systemic toxicity (repeated exposure)	No information available.
Chronic toxicity	Intentional misuse by deliberately concentrating and inhaling contents may be harmful or
	fatal. Chronic hydrocarbon abuse has been associated with irregular heart rhythms and potential cardiac arrest.
Target Organ Effects	Skin, Eyes, Respiratory System, and Central Nervous System.
Aspiration hazard	May be fatal if swallowed and enters airways.

Numerical measures of toxicity - Product Information

Unknown Acute Toxicity0% of the mixture consists of ingredient(s) of unknown toxicity.The following values are calculatedbased on chapter 3.1 of the GHS document .ATEmix (dermal)4915 mg/kgATEmix (inhalation-dust/mist)168.7 mg/l

12. ECOLOGICAL INFORMATION

Ecotoxicity

Chemical Name	Toxicity to algae	Toxicity to fish	Toxicity to	Toxicity to daphnia and	
			microorganisms	other aquatic invertebrates	
HEPTANE	-	375.0 mg/L LC50 Cichlid fish	-	-	
142-82-5		96h			
PROPANE/ISOBUTANE/N-	-	-	-	-	
BUTANE					
68476-86-8					

Persistence and degradability

Bioaccumulation

Chemical Name	log Pow
HEPTANE	4.66
142-82-5	
PROPANE/ISOBUTANE/N-BUTANE	2.8
68476-86-8	

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment	
Waste Disposal Methods	This material, as supplied, is a hazardous waste according to Federal regulations (40 CFR 261). Dispose of in accordance with federal, state, and local regulations.
Contaminated packaging	Do not re-use empty containers. Empty containers should be taken to an approved waste handling site for recycling or disposal. Pressurized container: Do not pierce or burn, even after use.

14. TRANSPORT INFORMATION

DOT Ground

LIMITED QUANTITY

ΙΑΤΑ

UN1950, AEROSOLS, FLAMMABLE, 2.1, LTD .QTY.

IMDG

UN1950, AEROSOLS, 2.1, LTD. QTY.

15. REGULATORY INFORMATION

International Inventories

Chemical Name	TSCA	DSL/NDSL	EINECS/ELI NCS	ENCS	IECSC	KECL	PICCS	AICS
HEPTANE	Х	X	Х	Х	Х	Х	Х	Х
PROPANE/ISOBUTA NE/N-BUTANE	Х	Х	Х	х	Х	Х	Х	Х
PETROLEUM DISTILLATES	Х	Х	Х	Х	Х	Х	Х	Х

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

CHINA - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

U.S. Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

SARA 311/312 Hazard Categories	
Acute Health Hazard	Yes
Chronic Health Star Hazard	Yes
Fire Hazard	Yes
Sudden Release of Pressure Hazard	Yes
Reactive Hazard	No

Clean Water Act

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material.

U.S. State Regulations

California Proposition 65

This product does not contain chemical(s) known to the State of California to cause cancer , birth defects, or other reproductive harm.

No warning is required.

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
HEPTANE 142-82-5	Х	Х	Х
PETROLEUM DISTILLATES 8052-41-3	Х	X	X

EPA Pesticide Registration Number Not applicable

Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all the information required by the CPR.

16. OTHER INFORMATION					
<u>NFPA</u>	Health Hazard 2	Flammability 4	Instability 0	Physical and chemical hazards -	
HMIS	Health Hazard 2	Flammability 4	Physical Hazard 1	Personal protection B	
Prepared By	34136 M	n Jetway Corporation lyrtle Street MI 48184-0126			
Issuing date Revision Date Revision Note	25-Jan-2022 26-Jan-2022				

Disclaimer

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of Safety Data Sheet