

DS Series Locking Date Stamps 2027

Standard	DS Series Locking
DS 0422	DSL 0422
DS 0422-27	DSL 0422-27
DS 0422-NA	DSL 0422-NA
DS 0530	DSL 0530
DS 0530-27	DSL 0530-27
DS 0530-NA	DSL 0530-NA
DS 0632	DSL 0632
DS 0632-27	DSL 0632-27
DS 0632-NA	DSL 0632-NA
DS 0847	DSL 0847
DS 0847-27	DSL 0847-27
DS 0847-NA	DSL 0847-NA
DS 1057	DSL 1057
DS 1057-27	DSL 1057-27
DS 1057-NA	DSL 1057-NA
DS 1267	DSL 1267
DS 1267-27	DSL 1267-27
DS 1267-NA	DSL 1267-NA
DS 1687	DSL 1687
DS 1687-27	DSL 1687-27
DS 1687-NA	DSL 1687-NA
DS 20107	DSL 20107
DS 20107-27	DSL 20107-27
DS 20107-NA	DSL 20107-NA

- Available in 4mm to 20mm diameters
- Insert sits flush in body
- Axial locking provides secure positioning
- **Max mold temperature: Ø4mm: 662°F (350°C), Ø5 - 20mm: 932°F (500°C)**
- Shares dimensions with PCS Standard Date Stamps
- Does not have compatible or shared components with PCS Standard Date Stamps



Order DS Series Locking Date Stamps



- COMPONENTS CANNOT BE SHARED BETWEEN STANDARD DATE STAMPS AND DS SERIES LOCKING. THIS CHART IS FOR IDENTIFYING WHICH PART IS A DIRECT DIMENSIONAL REPLACEMENT.
- TO SWAP TO THE DS SERIES LOCKING DATE STAMP (DSL) FROM A STANDARD SERIES DATE STAMP ASSEMBLY (DS), THE ENTIRE STANDARD ASSEMBLY MUST BE REPLACED WITH A DS SERIES LOCKING ASSEMBLY (DSL)