


High-Flow Stainless Steel Cascade Tubes

PCS Company's High-Flow Stainless Steel Tubes offer high strength construction and durability. Flow rate is increased up to 300% when compared with standard tubes. High-Flow Stainless Steel Tubes are available in standard lengths of 12", 18", 24", 36".

Features:

- Unit of Measure - Inch
- Stainless construction for high strength and durability
- "J" Item number prefix indicates the next largest thread size




Item Number	Tube Thread Size	Tube O.D.	Tube I.D.	H Thread Length	A	L Length
HF072T-12	5-44	0.072	0.060	.125	.140	12
HF072T-18	5-44	0.072	0.060	.125	.140	18
HF072T-24	5-44	0.072	0.060	.125	.140	24
HF072T-36	5-44	0.072	0.060	.125	.140	36
HF093T-12	5-44	0.09	0.076	0.125	.140	12
HF093T-18	5-44	0.09	0.076	0.125	.140	18
HF093T-24	5-44	0.09	0.076	0.125	.140	24
HF093T-36	5-44	0.09	0.076	0.125	.140	36
HF125T-12	10-32	0.125	0.109	0.156	.203	12
HF125T-18	10-32	0.125	0.109	0.156	.203	18
HF125T-24	10-32	0.125	0.109	0.156	.203	24
HF125T-36	10-32	0.125	0.109	0.156	.203	36
HF187T-12	1/4-28	0.187	0.167	0.203	.255	12
HF187T-18	1/4-28	0.187	0.167	0.203	.255	18
HF187T-24	1/4-28	0.187	0.167	0.203	.255	24
HF187T-36	1/4-28	0.187	0.167	0.203	.255	36
HF250T-12	5/16-24	0.25	0.23	0.235	.290	12
HF250T-18	5/16-24	0.25	0.23	0.235	.290	18
HF250T-24	5/16-24	0.25	0.23	0.235	.290	24
HF250T-36	5/16-24	0.25	0.23	0.235	.290	36
HF312T-12	3/8-24	0.312	0.288	0.296	.359	12
HF312T-18	3/8-24	0.312	0.288	0.296	.359	18
HF312T-24	3/8-24	0.312	0.288	0.296	.359	24
HF312T-36	3/8-24	0.312	0.288	0.296	.359	36
HF375T-12	7/16-20	0.365	0.34	0.359	.437	12
HF375T-18	7/16-20	0.365	0.34	0.359	.437	18

High Flow Stainless Steel Cascade Tubes

PCS Company's High-Flow Stainless Steel Tubes offer high strength construction and durability. Flow rate is increased up to 300% when compared with standard tubes. High-Flow Stainless Steel Tubes are available in standard lengths of 12", 18", 24", 36".

Features:

- Unit of Measure - Inch
- Stainless construction for high strength and durability
- "J" Item number prefix indicates the next largest thread size




Item Number	Tube Thread Size	Tube O.D.	Tube I.D.	H Thread Length	A	L Length
HF375T-24	7/16-20	0.365	0.34	0.359	.437	24
HF375T-36	7/16-20	0.365	0.34	0.359	.437	36
HF437T-12	1/2-20	0.427	0.397	0.421	.500	12
HF437T-18	1/2-20	0.427	0.397	0.421	.500	18
HF437T-24	1/2-20	0.427	0.397	0.421	.500	24
HF437T-36	1/2-20	0.427	0.397	0.421	.500	36
HF500T-12	9/16-18	.500	.444	0.421	.531	12
HF500T-18	9/16-18	.500	.444	0.421	.531	18
HF500T-24	9/16-18	.500	.444	0.421	.531	24
HF500T-36	9/16-18	.500	.444	0.421	.531	36
JHF072T-12	10-32	0.072	0.060	.156	.203	12
JHF072T-18	10-32	0.072	0.060	.156	.203	18
JHF072T-24	10-32	0.072	0.060	.156	.203	24
JHF072T-36	10-32	0.072	0.060	.156	.203	36
JHF093T-12	10-32	0.09	0.076	0.156	.203	12
JHF093T-18	10-32	0.09	0.076	0.156	.203	18
JHF093T-24	10-32	0.09	0.076	0.156	.203	24
JHF093T-36	10-32	0.09	0.076	0.156	.203	36
JHF125T-12	1/4-28	0.125	0.109	0.203	.255	12
JHF125T-18	1/4-28	0.125	0.109	0.203	.255	18
JHF125T-24	1/4-28	0.125	0.109	0.203	.255	24
JHF125T-36	1/4-28	0.125	0.109	0.203	.255	36
JHF187T-12	5/16-24	0.187	0.167	0.235	.290	12
JHF187T-18	5/16-24	0.187	0.167	0.235	.290	18
JHF187T-24	5/16-24	0.187	0.167	0.235	.290	24
JHF187T-36	5/16-24	0.187	0.167	0.235	.290	36

High Flow Stainless Steel Cascade Tubes

PCS Company's High-Flow Stainless Steel Tubes offer high strength construction and durability. Flow rate is increased up to 300% when compared with standard tubes. High-Flow Stainless Steel Tubes are available in standard lengths of 12", 18", 24", 36".

Features:

- Unit of Measure - Inch
- Stainless construction for high strength and durability
- "J" Item number prefix indicates the next largest thread size



Item Number	Tube Thread Size	Tube O.D.	Tube I.D.	H Thread Length	A	L Length
JHF250T-12	3/8-24	0.25	0.23	0.296	.359	12
JHF250T-18	3/8-24	0.25	0.23	0.296	.359	18
JHF250T-24	3/8-24	0.25	0.23	0.296	.359	24
JHF250T-36	3/8-24	0.25	0.23	0.296	.359	36
JHF312T-12	7/16-20	0.312	0.288	0.359	.437	12
JHF312T-18	7/16-20	0.312	0.288	0.359	.437	18
JHF312T-24	7/16-20	0.312	0.288	0.359	.437	24
JHF312T-36	7/16-20	0.312	0.288	0.359	.437	36
JHF375T-12	1/2-20	0.365	0.34	0.421	.500	12
JHF375T-18	1/2-20	0.365	0.34	0.421	.500	18
JHF375T-24	1/2-20	0.365	0.34	0.421	.500	24
JHF375T-36	1/2-20	0.365	0.34	0.421	.500	36
JHF437T-12	9/16-18	.427	.397	0.421	.531	12
JHF437T-18	9/16-18	.427	.397	0.421	.531	18
JHF437T-24	9/16-18	.427	.397	0.421	.531	24
JHF437T-36	9/16-18	.427	.397	0.421	.531	36
JHF500T-12	5/8-18	.500	.444	0.421	.531	12
JHF500T-18	5/8-18	.500	.444	0.421	.531	18
JHF500T-24	5/8-18	.500	.444	0.421	.531	24
JHF500T-36	5/8-18	.500	.444	0.421	.531	36