

GDS-C92

The Goodway GDS-C92 offers the perfect balance of portability and performance for industrial descaling. Built with heavy-duty polyethylene and acid-proof components, it ensures long-lasting use. The innovative Flow Reversal Valve eliminates foam and gas buildup, significantly speeding up descaling. Now featuring a freshwater flush update, the unit includes two additional ports for easy water intake and discharge without removing circulation hoses—just adjust the valves for a seamless flushing process. Self-priming and user-friendly, the GDS-C92 efficiently handles small to medium boilers, chillers, and heat exchangers with a 21 GPM flow rate.

GDS-C92 Scale Removal System includes:

- GDS-C92 Scale Removal System with 15-gallon tank
- Multiple fittings, two 10' circulation hoses, one dump hose, one water inlet hose, and one overflow hose

Features

- Acid proof pump and fittings
- Innovative flow reversal valve for faster cleaning
- Run dry, 21 GPM pump
- Compact design for easy transport and storage
- 15-gallon reservoir tank
- Integrated fresh water flush
- Venting cap for closed systems
- CE Certified
- Motor Power: 3/4 HP
- Input Power: 8.6 amps, 115 V, 60 Hz AC
- Water Flow: 21 GPM
- Pumps: Centrifugal
- Dimensions: 35" high x 15" wide x 23" deep
- Weight: 50 lbs net dry



| Item Number | GPM | Tank Capacity | Motor Power | Input Power | Height | Width | Depth | Weight (dry) |
|-------------|-----|---------------|-------------|--------------------------|--------|-------|-------|--------------|
| GDS-C92-FWF | 21 | 15 | 3/4 HP | 8.6 Amps, 115V. 60 Hz AC | 35" | 15" | 23" | 50 lbs |

GDS-C40

The Goodway GDS-C40 offers portable yet powerful descaling with a 15 GPM flow rate. Built with heavy-duty polyethylene and acid-proof components, it ensures durability for industrial applications. Its innovative Flow Reversal Valve eliminates foam and gas buildup, speeding up scale removal. The self-priming unit securely contains chemicals in its integral tank for safe, user-friendly operation. Ideal for oil coolers, heat exchangers, vacuum pumps, marine pumps, and more, it can also circulate glycol and antifreeze for winterizing heating and chilled systems.

GDS-C40 Scale Removal System includes:

- GDS-C40 Scale Removal System w/10-gallon tank
- Standard hose fittings
- Two (2) 10' circulation hoses

Features

- Acid proof pump and fittings
- Innovative flow reversal valve
- Run dry, or 15 GPM pump
- Compact design for easy transport and storage
- 10-gallon reservoir tank
- Venting cap for closed systems
- CE certified
- Motor Power: 1/2 HP
- Input Power: 7.6 amps, 115 V, 60 Hz AC (options available)
- Output Water Flow: 15 GPM
- Pump: Centrifugal
- Dimensions: 27" high x 15" wide x 17" deep
- Weight: 37 lbs net dry



| Item Number | GPM | Tank Capacity | Motor Power | Input Power | Height | Width | Depth | Weight (dry) |
|-------------|-----|---------------|-------------|--------------------------|--------|-------|-------|--------------|
| GDS-C40 | 15 | 10 | 1/2 HP | 7.6 Amps, 115V. 60 Hz AC | 27" | 15" | 17" | 37 lbs |

ScaleBreak® Liquid Descaler

ScaleBreak® by Goodway quickly and safely dissolves mineral deposits like limescale and struvite. This biodegradable industrial descaler removes calcium, rust, and other buildup from water-cooled and heated equipment, including chiller tubes, boilers, and heat exchangers. Safe for various metals, plastics, and rubber, it enhances efficiency and extends equipment life. Fortified with low-foaming agents, ScaleBreak is ideal for descaling boilers, chillers, condensers, cooling towers, oil coolers, furnaces, and more. Available in 30, 55, 275, and 330-gallon sizes. Note: Check local, state, and federal rules for the disposal of any used chemical/water in your area.

Features

- Recommended for all metals, except stainless steel
- Safely removes limescale, rust, struvite, and other deposits
- Fortified with powerful low foaming, wetting, and penetrating agents and superior corrosion inhibitors
- Use on boilers, all types of heat exchangers, chillers, and more
- Dissolves 2.0 lbs of scale per gallon of product
- Available in a variety of sizes

| Item Number | Container Size | Weight |
|----------------|----------------|----------|
| SCALEBREAK-5 | 5 Gallon | 47 lbs |
| SCALEBREAK-30 | 30 Galon | 50 lbs |
| SCALEBREAK-55 | 55 Gallon | 510 lbs |
| SCALEBREAK-275 | 275 Gallon | 2600 lbs |
| SCALEBREAK-330 | 330 Gallon | 3100 lbs |



ScaleBreak®-SS Liquid Descaler

ScaleBreak-SS by Goodway is a biodegradable industrial descaler specifically formulated for stainless steel. Free of hydrochloric acid (HCL), it delivers fast, effective scale and struvite removal without risking hydrogen embrittlement, ensuring long-term stainless steel protection. In today's industrial environment, unexpected shutdowns from scale buildup can be costly. Preventative maintenance is crucial for heat transfer, energy efficiency, and equipment longevity. ScaleBreak-SS dissolves limescale, struvite, and other deposits into a liquid suspension for easy flushing from water-operated systems. Available in 30, 55, 275, 330-gallon sizes. Note: Check local, state, and federal rules for the disposal of any used chemical/water in your area.

Features

- Use for the removal of calcium, limescale, rust, struvite, and other deposits.
- Designed for Stainless Steel applications
- Contains no HCL (Hydrochloric Acid)
- Fortified with powerful, low foaming, wetting, and penetrating agents and superior corrosion inhibitors
- Use in heat exchangers, boilers, and other stainless steel applications
- Available in 5, 30, 55, 275-gallon and 330-gallon sizes

| Item Number | Container Size | Weight |
|-----------------|----------------|----------|
| SCALEBRK-SS-5 | 5 Gallon | 50 lbs |
| SCALEBRK-SS-30 | 30 Galon | 300 lbs |
| SCALEBRK-SS-55 | 55 Gallon | 600 lbs |
| SCALEBRK-SS-275 | 275 Gallon | 2750 lbs |
| SCALEBRK-SS-330 | 330 Gallon | 3300 lbs |



ScaleBreak®-MP Liquid Descaler

ScaleBreak®-MP from Goodway is a biodegradable descaler formulated with citric acid, corrosion inhibitors, and penetrating agents for safe and effective scale removal. Designed for various metals, plastics, and stainless steel, it cleans quickly without compromising equipment integrity. Free of hydrochloric acid (HCL), ScaleBreak®-MP dissolves scale deposits into a liquid suspension for easy flushing, ensuring no residue is left behind. Safe for prolonged stainless steel exposure, it also prevents hydrogen embrittlement. Available in 55, 275, 330-gallon sizes. Note: Check local, state, and federal rules for the disposal of any used chemical/water in your area.

Features

- Contains no HCL (Hydrochloric Acid)
- Safe for stainless steel applications
- Fortified to deliver high powered descaling while protecting base materials from excessive corrosion
- Use in heat exchangers, chillers, boilers, pumping systems, cooling towers, FGD systems and more
- Designed for descaling applications in HVAC, industrial and maritime
- Dissolves 2.5 lbs of scale per gallon of product
- Available in 55, 275-gallon and 330-gallon sizes

| Item Number | Container Size | Weight |
|-----------------|----------------|----------|
| SCALEBRK-MP-5 | 5 Gallon | 50 lbs |
| SCALEBRK-MP-30 | 30 Galon | 300 lbs |
| SCALEBRK-MP-55 | 55 Gallon | 600 lbs |
| SCALEBRK-MP-275 | 275 Gallon | 2750 lbs |
| SCALEBRK-MP-330 | 330 Gallon | 3300 lbs |

