

## Metric Grade 8 Hex Head Bolts

PCS Company's Metric Grade 8 Hex Head Bolts range in thread sizes from M12-1.75 to M30-3.5 and lengths under the head from 50mm to 200mm.

### Features:

- Unit of Measure - Millimeters
- Hardness: 34-37 HRC
- 150,000 PSI Tensile Strength
- Black Finish



Item Number	Thread	Length Under Head	Hardness (HRC)	Tensile (PSI)	Wrench Size Required
M1217550	M12-1.75	50 mm	34-37	150,000	19 mm
M1217565	M12-1.75	65 mm	34-37	150,000	19 mm
M1217575	M12-1.75	75 mm	34-37	150,000	19 mm
M1217590	M12-1.75	90 mm	34-37	150,000	19 mm
M14290	M14-2.0	90 mm	34-37	150,000	22 mm
M142110	M14-2.0	110 mm	34-37	150,000	22mm
M16250	M16-2.0	50 mm	34-37	150,000	24 mm
M16260	M16-2.0	60 mm	34-37	150,000	24 mm
M16275	M16-2.0	75 mm	34-37	150,000	24 mm
M16290	M16-2.0	90 mm	34-37	150,000	24 mm
M162110	M16-2.0	110 mm	34-37	150,000	24 mm
M20255	M20-2.5	50 mm	34-37	150,000	30 mm
M202575	M20-2.5	75 mm	34-37	150,000	30 mm
M202590	M20-2.5	90 mm	34-37	150,000	30 mm
M2025110	M20-2.5	110 mm	34-37	150,000	30 mm
M2025130	M20-2.5	130 mm	34-37	150,000	30 mm
M2025150	M20-2.5	150 mm	34-37	150,000	30 mm
M24390	M24-3.0	90 mm	34-37	150,000	36 mm
M243110	M24-3.0	110 mm	34-37	150,000	36 mm
M243120	M24-3.0	120 mm	34-37	150,000	36 mm
M243150	M24-3.0	150 mm	34-37	150,000	36 mm
M243180	M24-3.0	180 mm	34-37	150,000	36 mm
M243200	M24-3.0	200 mm	34-37	150,000	36 mm
M3035120	M30-3.5	120 mm	34-37	150,000	46 mm
M3035150	M30-3.5	150 mm	34-37	150,000	46 mm
M3035180	M30-3.5	180 mm	34-37	150,000	46 mm
M3035200	M30-3.5	200 mm	34-37	150,000	46 mm