SAFETY DATA SHEET.

Issuing date 07-Jan-2015 Revision Date 08-Mar-2022 Version 2.03

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier

Product name PR1400 PAINTABLE MOLD RELEASE

Recommended use of the chemical

and restrictions on use

Product code F01488

Product Type Extremely Flammable Aerosol

Synonyms None

Supplier's details

Recommended Use Mold Release Agent.

Uses advised against No information available

Manufactured For: Manufacturer

PCS Company American Jetway Corporation

34500 Doreka Drive 34136 Myrtle Street
Fraser, MI 48206 Wayne, MI 48184-0126
PHONE;1-800-521-0546 M-F 8-5 PM Phone:(734) 721-5930

Emergency telephone number

Chemical Emergency Phone CHEMTREC: 1-800-262-8200 ID 1195 (UNITED STATES)

Number

2. HAZARDS IDENTIFICATION

Classification

Skin corrosion/irritation	Category 2
Specific target organ toxicity (single exposure)	Category 3
Aspiration toxicity	Category 1
Flammable Aerosols	Category 1
Gases under pressure	Compressed Gas

GHS Label elements, including

precautionary statements

Emergency Overview

DANGER

Hazard Statements

Causes skin irritation.

May cause drowsiness or dizziness.

May be fatal if swallowed and enters airways.

Extremely Flammable Aerosol

Contains gas under pressure; may explode if heated



Appearance Clear Physical state Aerosol Odor Solvent

Precautionary Statements - Prevention

Wash hands thoroughly after handling

Wear protective gloves.

Avoid breathing fumes, gas, mist, vapors, spray.

Use only outdoors or in a well-ventilated area.

Keep away from heat, sparks, open flames, hot surfaces - No smoking.

Do not spray on an open flame or other ignition source.

Pressurized container: Do not pierce or burn, even after use.

Precautionary Statements - Response

IF ON SKIN: Wash with plenty of soap and water.

If skin irritation occurs: Get medical advice, attention.

Take off contaminated clothing and wash it before reuse.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Call a POISON CENTER or doctor, physician if you feel unwell.

IF SWALLOWED: Immediately call a POISON CENTER, doctor, physician.

Do NOT induce vomiting.

Precautionary Statements - Storage

Store locked up.

Store in a well-ventilated place. Keep container tightly closed.

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

Precautionary Statements - Disposal

Dispose of contents, container to an approved waste disposal plant.

Hazards not otherwise classified (HNOC)

None

Other information

0% of the mixture consists of ingredient(s) of unknown toxicity.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No	Weight %*
HEPTANE	142-82-5	50-60
PROPANE/ISOBUTANE/N-BUTANE	68476-86-8	40-50

^{*}The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

First aid measures for different exposure routes

General advice Avoid contact with eyes, skin, and clothing. Avoid breathing vapors, mist, or gas.

Eye contact Rinse immediately with plenty of water and seek medical advice.

Skin contact Wash off immediately with plenty of water. If skin irritation persists, call a physician.

Inhalation Move to fresh air. If not breathing, give artificial respiration. If breathing has stopped,

contact emergency medical services immediately.

Ingestion Do NOT induce vomiting. Call a physician immediately. Never give anything by mouth to

unconscious person. Risk of product entering the lungs on vomiting after ingestion.

Most important symptoms/effects, acute and delayed

Main Symptoms Causes skin irritation. May cause eye and respiratory irritation. Harmful and may be fatal if

swallowed and enters airways.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Water fog. Dry chemical. Foam. Carbon dioxide (CO2). Cool containers / tanks with water spray.

Unsuitable Extinguishing Media Do not use a solid water stream as it may scatter and spread fire.

Specific hazards arising from the chemical

Extremely Flammable / Flammable. Keep product and empty container away from heat and sources of ignition.

Explosion Data

Sensitivity to Mechanical Impact none. Sensitivity to Static Discharge Yes.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Use shielding to protect fire-fighters from bursting containers.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions

Use with adequate ventiliation to keep the exposure levels below the OELS.

Environmental precautions

Environmental precautions Vapors can accumulate in low areas. Prevent further leakage or spillage if safe to do so. Do

not allow material to contaminate ground water system. Prevent product from entering

drains. Report spills as required by local and federal regulations.

Methods and materials for containment and cleaning up

Methods for Containment Prevent further leakage or spillage if safe to do so. Do not allow material to contaminate

ground water system. Prevent product from entering drains.

Methods for cleaning up Soak up with inert absorbent material. Contain liquid and collect with an inter,

non-combustible material. Pick up and transfer to properly labeled containers. Clean contaminated surface thoroughly. After cleaning, flush away traces with water. Prevent product from entering drains. Take precautionary measures against static discharges.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Avoid contact with eyes. Avoid breathing vapors or mists. Contents under pressure. Do not

puncture or incinerate cans. Do not stick pin or any other sharp object into opening on top of can. Avoid skin contact. Use with adequate ventilation. Keep container away from heat, flames, and all other sources of ignition. Keep can away from all sources of electricity such

as electric motors and batteries. Do not spray on hot surfaces.

Conditions for safe storage, including any incompatibilities

Technical measures/Storage

conditions

Keep containers tightly closed in a dry and well-ventilated place. Keep away from open flames, hot surfaces and sources of ignition .Keep in properly labeled containers. Keep out

of the reach of children. Store locked up.

Incompatible products Strong acids, alkalis, oxidizing agents.

Aerosol Level 3

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH	
HEPTANE STEL: 500 ppm		TWA: 500 ppm	IDLH: 750 ppm	
142-82-5	TWA: 400 ppm	TWA: 2000 mg/m ³	Ceiling: 440 ppm 15 min	
		(vacated) TWA: 400 ppm	Ceiling: 1800 mg/m ³ 15 min	
		(vacated) TWA: 1600 mg/m ³	TWA: 85 ppm	
		(vacated) STEL: 500 ppm	TWA: 350 mg/m ³	
		(vacated) STEL: 2000 mg/m ³	-	
PROPANE/ISOBUTANE/N-BUTANE 74-98-6: TWA: 1000 ppm		74-98-6:TWA: 1000 ppm	74-98-6:IDLH: 2100 ppm	
68476-86-8	106-97-8: STEL: 1000 ppm	TWA: 1800 mg/m ³	TWA: 1000 ppm	
	75-28-5: STEL: 1000 ppm	(vacated) TWA: 1000 ppm	TWA: 1800 mg/m ³	
		(vacated) TWA: 1800 mg/m ³	106-97-8:TWA: 800 ppm	
		106-97-8: (vacated) TWA: 800	TWA: 1900 mg/m ³	
		ppm	75-28-5:TWA: 800 ppm	
		(vacated) TWA: 1900 mg/m ³	TWA: 1900 mg/m ³	

F01488 - PR1400 PAINTABLE MOLD RELEASE

Revision Date 08-Mar-2022

ACGIH: (American Conference of Governmental Industrial Hygienists)

OSHA: (Occupational Safety & Health Administration) NIOSH IDLH: Immediately Dangerous to Life or Health

Other Exposure Guidelines Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962

(11th Cir., 1992).

Exposure controls

Engineering Measures Showers, eyewash stations, and ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/Face Protection Safety glasses with side-shields. Tightly fitting safety goggles.

Skin and body protection Chemical resistant apron. Protective gloves.

Respiratory protection If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved

respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be

provided in accordance with current local regulations.

Hygiene measures Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and chemical properties

Physical state Aerosol

AppearanceClearOdorSolvent

Color Clear Odor Threshold

<u>Property</u> <u>Values</u> <u>Remarks • Methods</u>

pH No information available
Melting/freezing point No information available

Boiling point/boiling range

Flash Point -104.4 °C / -156 °F Based on propellant

Evaporation rate No information available Flammability (solid, gas) No information available

Flammability Limits in Air upper flammability limit lower flammability limit

Vapor pressure Vapor density

Specific Gravity 0.652

Water solubility Practically insoluble

Partition coefficient: n-octanol/water

Autoignition temperature No information available

Decomposition temperature

Viscosity No information available

Explosive properties

Other information

 VOC Content(%)
 98.81

 MIR Value
 1.03

MIR Coating Category MRC - Mold Release Coating MAX 1.10 MIR

10. STABILITY AND REACTIVITY

Reactivity

No data available

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Conditions to Avoid

Extremes of temperature and direct sunlight.

Incompatible Materials

Strong acids, alkalis, oxidizing agents.

Hazardous Decomposition Products

Carbon oxides, Hydrocarbons, Fumes.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information Product does not present an acute toxicity hazard based on known information

Inhalation Exposure to high vapour concentrations may cause nervous systems effects such as

headache, nausea, and dizziness. May cause respiratory tract irritation.

Eye contact May cause slight irritation.

Prolonged skin contact may defat the skin and produce dermatitis. Skin contact

Harmful and may be fatal if swallowed and enters airways. Ingestion

Component Information

Component information							
Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation				
HEPTANE	-	= 3000 mg/kg (Rabbit)	= 103 g/m ³ (Rat) 4 h				
142-82-5							

Information on toxicological effects

Symptoms Causes skin and eye irritation. May cause respiratory irritation. May cause drowsiness and

dizziness. Harmful and may be fatal if ingested and enters airways.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Causes skin irritation. Eye damage/irritation May cause eye irritation.

Sensitization

Germ cell mutagenicity None known.

Carcinogenicity

Reproductive toxicity The ingredients are not reproductive hazards.

Specific target organ systemic toxicity (single exposure)

May cause drowsiness and dizziness.

Specific target organ systemic toxicity (repeated exposure)

No known effect based on information supplied.

Chronic toxicity

Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal. Chronic hydrocarbon abuse has been associated with irregular heart rhythms and

potential cardiac arrest.

Target Organ Effects

Skin, Respiratory System, and Central Nervous System.

Aspiration hazard May be fatal if swallowed and enters airways.

Numerical measures of toxicity - Product Information

Unknown Acute Toxicity 0% of the mixture consists of ingredient(s) of unknown toxicity.

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral) 4717 mg/kg ATEmix (dermal) 5991 mg/kg ATEmix (inhalation-vapor) 47 mg/l

12. ECOLOGICAL INFORMATION

Ecotoxicity

Chemical Name	Toxicity to algae	Toxicity to fish	Toxicity to	Toxicity to daphnia and
			microorganisms	other aquatic invertebrates
HEPTANE	-	375.0 mg/L LC50 Cichlid fish	-	-
142-82-5		96h		
PROPANE/ISOBUTANE/N-	-	-	-	-
BUTANE				
68476-86-8				

Persistence and degradability

•

Bioaccumulation

•

Chemical Name	log Pow
HEPTANE	4.66
142-82-5	
PROPANE/ISOBUTANE/N-BUTANE	2.8
68476-86-8	

Other adverse effects No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment

Waste Disposal Methods Dispose of in accordance with federal, state, and local regulations.

Contaminated packaging Do not re-use empty containers.

14. TRANSPORT INFORMATION

DOT Ground UN 1993, FLAMMABLE LIQUID, N.O.S.(XYLENE, ISOPROPYL ALCOHOL), 3, PG III

or

LIMITED QUANTITY

IATA UN 1992, FLAMMABLE LIQUIDS, N.O.S.(DICHLOROMETHANE, METHANOL,

TOLUENE),3,6.1,PGII

IMDG UN 1993, FLAMMABLE LIQUID, N.O.S.(XYLENE, ISOPROPYL ALCOHOL), 3, PG III

15. REGULATORY INFORMATION

International Inventories

Chemical Name	TSCA	DSL/NDSL	EINECS/ELI NCS	ENCS	IECSC	KECL	PICCS	AICS
HEPTANE	Χ	X	X	X	X	Χ	Χ	X
PROPANE/ISOBUTA NE/N-BUTANE	Х	Х	Х	х	Х	Х	Х	Х

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

CHINA - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

U.S. Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does contain a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Star Hazard	Yes
Fire Hazard	Yes
Sudden Release of Pressure Hazard	Yes
Reactive Hazard	No

Clean Water Act

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material.

U.S. State Regulations

California Proposition 65

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
HEPTANE	X	X	X
142-82-5			

EPA Pesticide Registration Number Not applicable

Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all the information required by the CPR.

16. OTHER INFORMATION

NFPA Health Hazard 2 Flammability 4 Instability 0 Physical and chemical

hazards -

HMIS Health Hazard 2 Flammability 4 Physical Hazard 1 Personal protection B

Prepared By American Jetway Corporation

34136 Myrtle Street Wayne, MI 48184-0126

Issuing date07-Jan-2015Revision Date08-Mar-2022

Revision Note

(M)SDS sections updated 1

Disclaimer

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of Safety Data Sheet