

INSERT STEELS

10 Steel Types | Custom sizes | 6 side milled to your dimension Plus .010 oversize total (+.004/-0) | Ships in 2-3 days



NAK 55®

NAK55 is a 40 HRC pre-Hardened, high performance, high precision, mold steel.

NAK 80®

NAK80 is a 40 HRC pre-Hardened, high performance, high precision, high polish mold steel.

PX5®

PX5 is a modified P20, high performance, high precision, mold steel.

Superplast® Stainless

Superplast® Stainless is a prehardened, free-machining, stainless mold steel specially designed for plastic mold bases.

TOOLOX 44®

TOOLOX 44 is a new quenched and tempered tool steel designed to have high impact and low residual stresses and therefore good dimensional stability.

TOOLOX 33®

TOOLOX 33 is a quenched and tempered tool steel designed to have low residual stresses and extremely good machinability.

DCMX®

DCMX is a matrix-type cold work tool steel: only fine carbides are distributed in matrix due to optimum alloy design and production process. DCMX shows high performance in service and ease in mold making.

S-Star® 420 ESR

420 ESR Stainless Steel Stocked in the pre-hardened condition (30-34 HRC) can be heat treated to 50-53 HRC

DHA-World® H-13

DHA-World is a high hardenability and high tough general use hot work die steel.

DH2F®

DH2F is a modified H-13, prehardened 37-41 HRC.

**Ships in
2-3 Days!**

10
Steel Types

**CUSTOM
SIZES**

**QUOTE
TODAY**

**Scan
for
more**



Visit www.pcs-company.com

Phone: 800-521-0546 | E-mail: customcomponents@pcs-company.com